

TY-RAP®

Fascetta in poliammide 6.6 con dentino di bloccaggio in acciaio inossidabile amagnetico

Temperatura d'esercizio : -40°C a +85°C

Autoestinguenza UL94 V2

Conforme alla norme UL (N° E49405) , Germanischer Lloyd

Conforme alla norme Lloyd Register of Shipping, Norske Veritas

Conforme alla norme MIL MS-3367-*



TY-RAP BIANCHE

Colore naturale	Tenuta min. alla trazione	larghezza [mm]	lunghezza [mm]	spessore [mm]	Ø cavo Min-Max [mm]
TY523MR	80 N	2,4	92	1,0	2 - 16
TY5232MR	80 N	2,4	200	1,0	2 - 50
TY5234MR	80 N	2,4	356	1,0	2 - 102
TY524MR	180 N	3,6	140	1,1	2 - 29
TY5242MR	180 N	3,6	208	1,1	2 - 50
TY526MR	180 N	3,6	281	1,1	2 - 76
TY5244MR	180 N	3,6	368	1,1	2 - 103
TY525MR	220 N	4,8	186	1,1	3,5 - 45
TY5253MR	220 N	4,8	293	1,1	3,5 - 78
TY528MR	220 N	4,8	360	1,1	3,5 - 102

Ty-Rap®

Premium cable ties with steel locking barb
Standard ties

Product overview

The main characteristics of the Ty-Rap® cable ties are shown on pages 8 and 9.

To cover the most demanding applications, the standard Ty-Rap® cable ties are available in:

- Several lengths
- 6 typical widths, with a tensile strength up to 780N
- 6 different materials, with a total of 9 different grades (see pages 102 to 109 for material specifications & selection)
- Several colours and packaging sizes (see page 10)

Approvals



E49405



Technical Information

Material	Polyamide 6.6
Temperature range	-40°C to +85°C
Colour	Natural
Flammability rating	UL 94 V-2
Other properties	Halogen free, Silicone free

