



CONVERTITORE MEDIA & MODULO

Standard & protocolli	IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z
Funzionalità di base	Auto-negotiation of Half-Duplex / Full-Duplex transfer mode Extends fiber distance up to 0.55km using 50/125um fiber Extends fiber distance up to 0.22km using 62.5/125um fiber
Porte	1 1000M SC/UPC port 1 1000M RJ45 port (Auto MDI/MDIX)
Lunghezza d'onda	850nm
Network Media 1000BASE-SX	Multi-mode Fiber
Network Media 1000BASE-T	UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
LED	PWR, LINK, RX
Dimensioni (L x P x A)	3.7*2.9*1.1 in. (94.5*73.0*27.0 mm)
Alimentazione	External Power Adapter
Massimo consumo di energia	1.66W
Sicurezza & emissioni	FCC, CE, RoHS
Package Contents	<ul style="list-style-type: none"> • Media Converter MC200CM • Power Adapter • Installation Guide
Ambiente	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing